



CHISAGE ESS

BATTERY PACK

MOON15-G



Product Features

- High inverter compatibility
 - Safe LiFePO4 rechargeable battery
 - Support Max. 15pcs batteries in parallel
 - LCD for easy viewing of data
 - Support Bluetooth monitoring
 - Wheels on the bottom for easy movement
-

Technical Data

Model	MOON15-G
Nominal Energy (Wh)	15,360
Usable Energy (Wh)	13,800
Nominal Capacity (Ah)	300
Nominal Voltage (V)	51.2
Operation Voltage Range (V)	40V~58.4V
Standard Charge Current (A)	150
Standard Discharge Current (A)	150
Max. Charge Current (A)	150
Max. Discharge Current (A)	150
Cooling	Natural cooling
Operation Temperature	Charge Temperature: 0°C~55°C; Discharge Temperature: -20°C~55°C
Working Humidity	20~80%RH
Protection Degree	IP21
Dimension (mm)	550*269*957 (W*D*H)
Net Weight (kg)	135
Installation Type	Floor mounted
Certification	CE, UN38.3, ROHS
Communication	CAN, RS485
Lifetime	6,000 Cycles@80% DOD
Warranty	5 years

ZHEJIANG CHISAGE NEW ENERGY TECHNOLOGY CO., LTD.

Tel: +86 150 5749 1826 E-mail: info@chisagess.com

Add: No.1828, Fuqing South Road, Panhuo Street, Yinzhou District, Ningbo City, Zhejiang Province, China 315000