

PC1

Solar Konektör PC1

Teknik Veri	
İzasyon malzemesi	PPO
Beyan akımı	30A(2.5mm ²) 35A(4mm ²) 40A(6mm ²)
Voltaj değeri	1500V(TUV)
Karakteristik Temas Direnci	<0.5mohm
IP koruma sınıfı	IP68
Termal aralık	-40°C to +85°C
Yanmazlık sınıfı	UL94 - V0
İletken malzemesi	Kalay kaplı bakır
Kablo Kesitleri	2.5mm ² -4.0mm ² -6.0mm ²

AÇIKLAMA

1500V PC1 konektörü, IP68 Koruma sınıfı ve IEC 62852:2014, EN 50521:2015 standartına göre TÜV sertifikasına sahiptir. Gereken tüm solar uygulamalarda rahatlıkla kullanılır.

Solar Connector PC1

Technical Data	
Insulation material	PPO
Rated current	30A(2.5mm ²) 35A(4mm ²) 40A(6mm ²)
Rated voltage	1500V(TUV)
Charactertic Contact Resistance	<0.5mohm
Protection degree	IP68
Ambient temperature range	-40°C to +85°C
Flame class	UL94 - V0
Contact material	Copper , Tin plated
Cable cross sections	2.5mm ² -4.0mm ² -6.0mm ²

EXPLANATION

1500V PC1 solar connector has IP68 protection degree and TÜV certification according to IEC 62852:2014 , EN 50521:2015 standard. Ekinler PC1 connector can be safely used on all solar applications.

